









NOTES: UNLESS OTHERWISE SPECIFIED

- DIMENSIONS ARE IN INCHES (MM).
 MACHINED SURFACES TO BE 63 µIN MAX.

- MACHINED SORT ACES TO BE 65 µIN MAX.
 DO NOT SCALE DRAWING.
 PART TO BE FREE OF BURRS AND SHARP EDGES.
 ALL MATERIAL TO BE CLEAN, DEGREASED AND FREE OF ALL IMPURITIES.
 ANY CHANGE MUST BE AUTHORIZED BY AN SC&R ENGINEER.

MATERIAL TYPE: 316 SS **VENDOR ID:**

Α	3/26/2011	RELEASE FOR BUILD				GM	ER
REV	DATE	DESCRIPTION OF CHANGE	RIPTION OF CHANGE			BY	APPR
REVISIONS							
Stainless Cable & ANGU FRACT		.XX ±.01 UNLESS OTHERWISE ANGULAR ±0.5° SPECIFIED FRACTIONAL ±1/32	OF STAINLESS CABLE & RAILING AND IS PROTECTED UNDER COPYRIGHT LAW AS AN UNPUBLISHED WORK. IT MAY WOT BE PUBLISHED, COPIED,	DUNDER SAN Washer BRITINAY INCOPPED, WITHOUT O1-035cc-01		ed	SHEET
DRAWN BY: DATE: 3/26/2		I NOULUI.	EXPRESS WRITTEN PERMISSION FROM SC&R.			1 OF 1	